



Heavy Duty Twin 2m Elasticated Web Shock Absorbing Lanyard

ZABM-2T5EH

Maxisafe Advantages

- Twin Leg Shock Absorbing Lanyard with -
 - Shock absorber at harness end provides maximum force on user in the event of a fall 6kN
 - Suitable for weight range 60-140kG
 - Elasticated 44mm high strength tubular polyester webbing provides shorter relaxed length while moving around.
 - Abrasion resistant cover on loop ends to prevent damage from snap hooks
 - Double action locking mechanism to Snap and Scaffold Hooks provides double safe connection
 - 16Kn capacity Snap/Scaffold Hooks with 20mm/60mm gate size
 - Meets and Tested to AS/NZS1891.5:2020
 - Certified by BSI

Capacity

One person plus tools – 60kG to140kG

Compatibility

MAXISAFE lanyards should be used with compatible connectors which ensure connection will be maintained in the event of high forces on the gate

Product Specifications

Product Code	Description	Packaging	Barcode
ZABM-2T5EH	Heavy Duty Twin 2m Elasticated Web Shock Absorbing Lanyard	1	9341993001997



Applications

- For working in fall arrest situation, attached to front or rear attachment point on harness allowing movement across structure maintaining attachment and maximising freefall to 2m
 - Scaffold Work / Roof Work / Construction Work
 - Maintenance work on machinery
 - Use in accordance with AS/NZS1891.4:2009



AS 1891.5:2020
Lic. BMP 692698

04/2021 E&OE

[CLICK HERE FOR PRODUCT SPEC](#)

there's safe and there's Maxisafe.

Your Maxisafe Dealer: