

100A Single Phase Type A 4 Pole 6kA 300mA RCD with Time Delay


Product Ref: **100A4P300ATD**

Technical Features:

- Insulated DIN rail clips
- Sensitivity 300mA (6kA)
- 200 to 300ms Time Delay
- Test 'T' operating test button on the front panel
- Fault tripping indicator window

Product Specification

Bidirectional	Yes
Type	Type A
Voltage Rating	415V
Current Rating	100A
IP Rating	IP20
Weight	0.353kg
Incoming Terminal Capacity	35mm ²
Number of Modules	4
Number of Poles	4 Pole
Outgoing Terminal Capacity	35mm ²
Torque Settings	2.5Nm
Short Circuit Rating	6kA
Time Delay	Yes (200 - 300ms)
Tripping Sensitivity	300mA
RCD Type	A
Mounting	Din Rail
Material	Plastic
Colour	Grey/Blue
Compliance	UKCA, CE
Guarantee	1 Year
Standards	IEC 61008-1
Depth	65mm
Height	82.5mm
Width	72mm



Type A - Ai



Errors and omissions excepted (E&OE). All information is subject to change without notice and is correct at the time of print. Refer to issue number and date below.

Tel: +44 (0)1302 342 642 • mcg.co.uk • @mcg_industrial