

20A Double Pole Bidirectional Type A 10kA 30mA 2 Module B Curve RCBO

Product Ref: **20ADP30BAT**


Technical Features:

- Bidirectional
- Compact design allows for easier installation
- Commercial and residential applications such as EV charging units or air source heat pumps
- Two Module device that protects both live and neutral conductors
- Protection device combines the overcurrent function of an MCB with earth fault function of an RCD
- DIN rail mountable
- Incoming cables can be connected either at the top or the bottom
- Test button and trip indicator



Product Specification

Bidirectional	Yes
Voltage Rating	230V
Current Rating	20A
Weight	0.236kg
Incoming Terminal Capacity	25mm ²
Number of Modules	2
Number of Poles	2P
Outgoing Terminal Capacity	25mm ²
Torque Settings	2Nm
Short Circuit Rating	10kA
Tripping Characteristics	B Curve
Tripping Sensitivity	30mA
RCD Type	A
Mounting	Din Rail
Colour	Grey/Blue
Material	Plastic / Metal
Compliance	UKCA, CE
Guarantee	1 Year
Standards	BS EN 61009-1
Depth	66mm
Height	82.5mm
Width	36mm



Errors and omissions excepted (E&OE). All information is subject to change without notice and is correct at the time of print. Refer to issue number and date below.

Tel: **+44 (0)1302 342 642** • mcg.co.uk • [X@mcg_industrial](mailto:info@mcg_industrial)