

20 Way Metal Consumer Unit Isolator Controlled


Product Ref: **MMSB20**

Technical Features:

- Complete with fully fitted and pre-wired 2 pole 100A incoming isolator
- Ferruled cable ends for secure connections
- Fully enclosed metal construction body with drop-down metal cover. Raised keyholes for secure easy installation
- Multiple circular cable entry knockouts (M25, M32 and M40) plus rear aperture/rounded cable entries
- Finished in white polyester powder coating to RAL9010
- BS 7671 Amendment 3 and BS EN 61439-3 compliant

Product Specification

| | |
|-------------------------|------------------------------------|
| Voltage Rating | 230V |
| Current Rating | 100A |
| IP Rating | IP20 |
| Weight | 3.620kg |
| Incoming Device | Isolator |
| Number of Outgoing ways | 20 |
| Number of Modules | 20 |
| Cable Entry | Knockouts (M25, M32 and M40) |
| Supplied With | 1 x 100A 2 Pole Isolator |
| Type | Isolator Controlled |
| Mounting | Surface |
| Colour | White |
| Finish | Polyester Powder Coated |
| Material | Steel |
| Compliance | UKCA, CE |
| Guarantee | 1 Year |
| Standards | BS 7671 Amendment 3, BS EN 61439-3 |
| Depth | 110mm |
| Height | 235mm |
| Width | 450mm |



Errors and omissions excepted (E&OE). All information is subject to change without notice and is correct at the time of print. Refer to issue number and date below.

Tel: +44 (0)1302 342 642 • mcg.co.uk • [@mcg_industrial](https://twitter.com/mcg_industrial)