

2 Way Metal Consumer Unit RCD Controlled

Product Ref: **MMSB2R80AT**


Technical Features:

- Complete with fully fitted and pre-wired 80A 2 pole 30mA Type A RCD
- Ferruled cable ends for secure connections
- Fully enclosed metal construction body with drop-down metal cover. Raised keyholes for secure easy installation
- Multiple circular cable entry knockouts top (M25, M32 and M40) plus rear aperture/rounded cable entries
- Finished in white polyester powder coating to RAL9010
- IP20 protection
- BS EN 61439-3 compliant



Product Specification

Voltage Rating	230V
Current Rating	80A
IP Rating	IP20
Weight	1.496kg
Incoming Device	80A 30mA RCD
RCD Type	Type A
Tripping Sensitivity	30mA
Number of Outgoing ways	2
Cable Entry	Knockouts (M25, M32 and M40)
Supplied With	1 x 80A 2 Pole 30mA Type A RCD
Type	RCD Controlled
Mounting	Surface
Colour	White
Finish	Polyester Powder Coated
Door Type	Top Hinged
Material	Steel
Compliance	UKCA, CE
Guarantee	1 Year
Standards	BS EN 61439-3
Depth	110mm
Height	235mm
Width	125mm



Errors and omissions excepted (E&OE). All information is subject to change without notice and is correct at the time of print. Refer to issue number and date below.

Tel: +44 (0)1302 342 642 • mcg.co.uk • [@mcg_industrial](https://twitter.com/mcg_industrial)