

Installation Notes

These instructions should be read in full and retained after installation for future reference
 Before installation or maintenance is carried out, ensure that the mains supply is turned off, and adequately isolated.

SPECIFICATIONS

Voltage Range	220-240V
Frequency	50Hz
Contact Rating (Load)	16A Resistive Load 2A Inductive Load Volt Free Switching
Shortest Switching Time	1 Minute
Programming capacity	6 Programme Blocks
Number of Channels	1
Display	LCD
Backup Battery	100 Hours
Manual Switch	Yes
Mounting	DIN Rail
Manual Override	Yes
Connections	2.5mm ² max

IMPORTANT

This unit should be installed by a competent person in accordance with the current IEE Wiring Regulations. If in doubt consult a qualified electrician.

- Before connecting the timer to the mains, check that the mains voltage and frequency correspond to the rating plate (on side of timer).
- Do not overload. Refer to the Ampere rating (Amps) on the rating plate.
- Do not expose the timer to extremely high or low temperatures. Do not place the timer in direct sunlight.
- Do not allow the timer to come into contact with water.
- If the time switch is mounted near equipment where heat produced raises the local ambient temperature above 55°C, then a 1/2 module space should be left between the time switch and the equipment.
- If used to operate a contactor, then a 1 module space should be left between timer and contactor.

INSTALLATION

- This timer is designed to be din rail mounted.
- Ensure that the correct supply is connected to terminals 1 and 2.
- Terminals 3 and 4 are volt free contacts. Live in goes to terminal 3 and Live out goes to Load. There is no neutral switching with this model, ensure that maximum loading is complied with.

HOW TO OPERATE

When the timer is new or when it has not been used for some time it may need to be "charged". To do this, connect to power. The built-in rechargeable battery will begin to charge. When symbols appear in the display (after approx. 2 minutes), press the "Reset" button (use a pencil or pen).

Caution: this will cancel all memory including timer settings. The timer l be 'clean' for new commands. If a power failure should occur (or should the timer be disconnected from the power supply for a short time), the built-in rechargeable battery will then provide power to the clock and guarantee that the time and switching programmes are retained and not disturbed or lost.


HOW TO SET 24 HOUR CLOCK

Present time and day

1. Press and hold ☰ button during the entire "present time and day" setting procedure .
2. Set the present time using buttons "h+" and "m+" .

If you press and hold buttons "h+" and "m+" for longer than a second, the figures in the display will scroll continuously. Set the present day of the week using button "Day" .

3. Release ☰ button. The clock is now running. The flashing colon indicates this.



SWITCHING TIME(S)

You can set as many as six switching on commands and an equal number of corresponding switching off commands in the following manner:

1. Depress "Timer" button once. The actual time will disappear from the display. This Timer on indication will be displayed instead, denoting a vacant "on" time on No. 1 programme.

	TIMER
	ON
—	MO
—	TU
—	WE
••	TH
••	FR
—	SA
—	SU

NOTE: Setting hours and minutes: When setting switch on time and switch off time be sure to set minutes as well as hours, eg.: if **08 .00** is required, set all 4 digits: **08** and **00**.

2. Set the required switching-on time using button **h+** and **m+**.

...continued

SWITCHING TIME(S) - Continued


- Set the day(s). See **Day** button selection on which the switching-on command must be executed.
- Depress button **Timer** once. Timer off will be displayed.
- Set the required switching-off time using button **h+** and **m+**.
- Set the day(s) on which the switching off command must be executed. (Default setting is every day).
- Pressing the **Timer** button will move the timer to programme 2 ON.

When this 2 Timer on indication appears you can begin setting another switching on command, if you wish. Six such programmes may be stored in this manner, following 2 to 6 above.

After setting the required **ON** and **OFF** times, press ⊕ to revert to present time.

EXAMPLE


The switching commands will be carried out every day if no day or days have been set.



NOTE: Be sure that the desired day or days are chosen on both the **ON** and the **OFF** displays.

EXAMPLE

If a day or 'block' programme of days is chosen, the timer will respond to each of those days and omit the blanks.



'DAY' BUTTON SELECTIONS

Every day of the week

If you do not enter the day when setting a switching command, the switching will be carried out at the set time on every day of the week.

Only one day of the week

If you enter a particular day while setting a switching command (using button **Day**), the command will be carried out at the set time only on that specific day of the week.

Abbreviations

MO = Monday **TU** = Tuesday
WE = Wednesday **TH** = Thursday
FR = Friday **SA** = Saturday
SU = Sunday.

On a weekly combination (or 'block' programming) of days

When pressing button **Day** several times, you will find by means of the display that three combinations of days are also possible :

MO TU WE TH FR = Monday to Friday

SA SU = Saturday and Sunday

MO TU WE TH FR SA = Monday to Saturday

If you enter these combinations of days instead of one individual day, the on/off command will be carried out at the set time on each of the corresponding days of the week.

This programme will repeat itself week after week until the programme is changed or the timer is disconnected.

HOW TO CHECK, CHANGE OR DELETE SWITCHING COMMANDS

Checking

By pressing button **Timer** a number of times you can make the switching on and switching off commands visible in the display: first the set commands are presented and then the free spaces .

Changing

You can change a switching command by making it appear on the display and pressing **day**, **hour** and **minute** buttons accordingly.

Deleting

Delete a timer command period (an **ON** and **OFF** time) by pressing the **Timer** button until the required program number on time is displayed in the window and pressing **h+** until - - is displayed immediately after 23. Do the same with **m+** until -- appears after 59. Repeat this sequence for the **Off** mode.

The deleted command then becomes available for reprogramming. Press button **Timer** after changing or deleting a command to save the new command.

Switching back to present time

After setting the switching commands you return to normal time reading by pressing button.

Is power being supplied to connecting load?

The word **ON** or **OFF** in the display, above the time reading, informs you about the actual switching condition.

OVERRIDE SWITCH

When in the **OFF** mode pressing the button marked will switch **ON** the power to the load connected to the timer.

If the button is pressed again the power will switch off. If the button is not pressed again, power will remain on until the completion of the next on/off command when power will switch off.

If not pressed again, the power will remain off until the following **ON** command has been reached.

GUARANTEE

Your MCG 24/7 Digital DIN Rail Timer is guaranteed for 12 months from the date of purchase. This does not affect your statutory rights.