

DCM330

Fork Multimeter



- **200.0 A ac Open Jaw current measurement**
- **0.1 V to 1000 V auto-ranging ac and dc voltage measurement**
- **0.1 Ω to 20.00 M Ω resistance range**
- **Continuity buzzer and diode check**
- **Non-contact detection of AC voltage**
- **CAT III 1000V and CAT IV 600 V**

DESCRIPTION

The Megger DCM330 Fork Multimeter is a convenient, compact instrument designed to measure ac current up to 200 A, and perform the basic functions of a basic multimeter.

With ac and dc voltage measurements up to 1000 V and resistance measurements up to 20 M Ω , a non-contact voltage detection facility and a continuity buzzer with diode check, the Megger DCM330 is a truly versatile instrument. All of these features combined into a single compact instrument eliminate the need for separate multimeter and clampmeter.

The large central range knob enables ambidextrous single-handed use, and the separate voltage/resistance test leads can be disconnected when not in use.

The open-jaw design of the clampmeter enable simple and fast measurements to be made on single conductors up to 16mm diameter. With no moving clamp parts, the Megger DCM330 is not susceptible to dirt, grit or moisture around the cable, so is equally ideal for use in dirty trenches or trunking; or clean laboratory conditions. It provides average responding RMS values, and with the conductor(s) positioned centrally and squarely within the jaws, achieves readings of better than 3% accuracy.

The Megger DCM330 is auto-ranging on all ranges. Current measurement and the non-contact voltage sensor do not need the test leads; all other functions will require their use.

The voltage detection function can identify the presence of live AC voltages from 50 V to 1000 V at 50 to 500 Hz.

It is operational on any range including OFF. Voltage is capacitively detected, signalled by a tone sounding and the illumination of a red LED situated below the clamp head.

The Megger DCM330 is powered by 2 x AAA cells providing 250 hours of operation, and has an auto-off feature that activates after approximately 10 minutes.

The tough body provides easy and comfortable grip, providing durability while stored in a tool box or pocket. The DCM330 is designed to withstand a 1.22m (4 feet) drop without damage.

The display is a large 3½ digit LCD. In difficult or awkward locations, the display can be frozen with the "HOLD" function, removed from the cable under test and read independently.

ADDITIONAL FEATURES

- **Compact pocket sized design**
- **Auto power-off**
- **Supplied with detachable test leads and carry-case**

APPLICATIONS

The DCM330 is suitable for use anywhere where there is a requirement to measure ac current in single unshielded conductors less than 16mm diameter, or ac/dc voltages up to 1000 V, or resistances up to 20 MΩ.

Typical applications include domestic and industrial wiring installation fault-finding, basic load analysis, equipment commissioning and maintenance, machinery installations, etc.

Note: The non-contact Voltfinder function is intended to identify live cables within the jaws, and is not suitable for use on shielded conductors such as armoured cable or those within or behind metallic or conductive panels, in metal conduit, etc.

SPECIFICATION

(accuracies specified at 23°C)

AC current

Frequency	Range	Accuracy
50 - 60 Hz	0 - 200.0 A	±3% ±3 digits

Average sensing, RMS indicating

Overload protection: 400 A rms

AC/DC volts

Range	DC	AC
200.0 V	±1% ±2 digits	±1.5% ±5 digits
1000 V		50 Hz - 500 Hz

Input impedance: 2 MΩ (<100 pF)

Overvoltage protection: 1000 V

Resistance

Range	Accuracy
200.0 Ω	±1% ±5 digits
2.000 kΩ	±1% ±2 digits
20.00 kΩ	
200.0 kΩ	
2.000 MΩ	±1.9% ±5 digitsΩ
20.00 MΩ	

Overload protection: 600 V rms

Diode check

1 mV: ±1.5% ±0.05 V

Overvoltage protection: 600 V rms

Continuity

Buzzer operates: <50 Ω

Turns off: >250 Ω

Response time: 0.25 sec - 1 sec

Display

3 1/2 digit large LCD

2000 count

Sample rate: 1.5/sec

Overrange: "OL"

Auto power off

10 minutes after power on

Battery

R03 UM4 AAA 1.5 V x 2 (not suitable for rechargeable cells)

Life: 250 hours (alkaline cells)

Calibration: 12 months

Operating altitude: 2000 m

Operating temperature

0°C - 30°C (>80% RH)

30°C - 40°C (>75% RH)

40°C - 50°C (>45% RH)

Storage temperature

-20°C - +60°C (0 - 80% RH) (batteries not fitted)

Dimensions

54 mm (W) x 193 mm (H) x 31 mm (D)

Weight

280 g (battery installed)

Safety

IEC61010-1 1000 V CAT III

600 V CAT IV

EMC

EN 61326-1

Drop protection

1.2 m drop onto hard floor

ORDERING INFORMATION

Item (Qty)	Order Code
Fork Multimeter; 200A ac; 1000V dc	1000-219
Included accessories	
Batteries	
Pouch	
Test leads	
User guide	
Replacement test leads	
Red/black test leads with croc clips	6220-779
Red/black fused test leads (500 mA) with croc clips	6220-789

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
E uksales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1088 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399

OTHER TECHNICAL SALES OFFICES
Norristown USA, Sydney AUSTRALIA,
Toronto CANADA, Trappes FRANCE,
Kingdom of BAHRAIN, Mumbai
INDIA, Johannesburg SOUTH AFRICA
and Conjure THAILAND.

Registered to ISO 9001:2000 Cert no. Q 09290
Registered to ISO 14001-1996 Cert no. EMS 61597

DCM330_DS_en_V02

www.megger.com
Megger is a registered trademark