M12 FSCIWF14-252X

M12 FUEL™ ¼" SUB-COMPACT IMPACT WRENCH WITH FRICTION RING

- A weight of 0.86 kg with M12HB 2.5 Ah battery, a length of 112 mm, and a girth of 51 mm means better access to tight spaces and less user fatigue
- 95 Nm of fastening and 136 Nm of nut-busting torque to easily tackle most common tight space automotive applications
- Up to 3,800 RPMs for exceptional application speed
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- Mode 4 (Forward): Auto shut-off control applies no more than 9 Nm of torque for hand-tight fastening applications to prevent over-tightening
- Mode 4 (Reverse): Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- Trigger mode selection for easy one hand selection of speed settings
- Tri-LEDs for shadowless work area illumination
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



REDLITHIUM™



	M12 FSCIWF14-252X	Impact rate (ipm)
0-1,350 / 0-3,700 / 0-4,400 / 0-4,400	Max. torque (Nm)	
	Nut_busting torque [Nm]	
136	Weight with battery pack (EPTA) (kg)	
0.86 (M12 HB2.5)	Kit included	
2 x M12 HB2.5 Battery packs, C12 C Charger, HD Box	Article number	