



SMARTSWIPE™



DEXTERITY



HIGH VISIBILITY



HI-VIS CUT A GLOVES

FEATURES

- Fluorescent material provides high visibility in low light environment.
- Lightweight and thin gloves with polyurethane dipped palm.
- Designed to provide increased dexterity and all-day comfort, ideal for material Handling, Carpenter, Plumbing, remodeling, general contracting applications.
- SMARTSWIPE™ palm and fingertips - allows the use of touch screen devices without removing gloves.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3121A), UKCA.

TECHNICAL INFORMATION

CUT LEVEL (COLOR CODE):
CUT LEVEL A (WHITE)

COLOR OF THE GLOVE:
RED

MATERIAL:
POLYESTER, HPPE, GLASS FIBER, COOPER FIBER.
COATING: POLYURETHANE (PU)

GAUGE:
15

SIZE RANGE:
HI-VIS CUT A GLOVES - AVAILABLE FROM SIZE 7/S TO 11/ XXL

UNIT GUIDE

SIZE	HANG CARD			12 PACK			GIFT BOX		
	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/MASTER)	ARTICLE NUMBER	NO. OF PAIRS	PACKAGING (INNER/MASTER)
7 / S	4932479916	1	6/120		12	12/144		144	12/144
8 / M	4932479917	1	6/120		12	12/144		144	12/144
9 / L	4932479918	1	6/120		12	12/144		144	12/144
10 / XL	4932479919	1	6/120		12	12/144		144	12/144
11 / XXL	4932479920	1	6/120		12	12/144		144	12/144



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu



SMARTSWIPE™



DEXTERITY



HIGH VISIBILITY



HI-VIS CUT A GLOVES

CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,
MAXIMUM WASHING
TEMPERATURE 40° CELSIUS



NO CHEMICAL
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER



MAX. 5 WASHING
CYCLES

STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity or rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level ≥ 1 then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.
STAY PRODUCTIVE.**

Disclaimer
Information present within
this sheet was correct at
the date of issue.

Techtronic Industries GmbH
71364 Winnenden
Germany
milwaukeetool.eu