




# DATASHEET



## BATM4

230V 4ft 20W Modular LED Batten - 4000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	BATM4
DESCRIPTION	230V 4ft 20W Modular LED Batten - 4000K
NET WEIGHT (KG)	1.2
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Height - 70 Width - 61
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
WATTAGE (W)	20
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2800
LUMENS LIGHT SOURCE ONLY (LM)	2850
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	136
CIRCUIT WATTAGE (W)	20.7
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
RUNNING CURRENT (A)	0.095
DISPLACEMENT FACTOR	>0.7
SVM	0
PST-LM	0.01
BEAM ANGLE (DEGREES)	125
L70B50 LIFESPAN (HRS)	100000



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.  
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.





<b>DIMMABLE</b>	No
<b>EMERGENCY CONVERSION KIT</b>	MODEMKIT
<b>OPERATING TEMPERATURE</b>	-20~45°C
<b>INPUT VOLTAGE</b>	230V 50Hz
<b>CABLE GLAND INCLUDED</b>	No
<b>DRIVER</b>	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 54-114V OUTPUT CURRENT - 350mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 91.5 AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 85°C
<b>WARRANTY</b>	5year(s)
<b>MANUFACTURED IN ACCORDANCE WITH</b>	BS EN 60598
<b>ORIGIN OF MANUFACTURE</b>	China
<b>DECLARATION OF CONFORMITY (HELD ON FILE)</b>	Yes
<b>EAN</b>	5056270852592

Date Created: 16/10/2024 09:44

