



Data Specification Sheet



HPLED1 Mini LED Ground Light

Code	HPLED1W & HPLED1B
Description	1w High Powered Mains Led Built in Driver IP65 available in White or Blue
Finishes available	Stainless Steel
Dimensions (mm) Length Diameter Sleeve	90(L)mm 62(Dia)mm
Dimensions (mm) Length Diameter Luminaire	Body - 70(L)mm – 39(Dia)mm Bezel - Diameter – 62mm
Cut-out	60mm (with sleeve) 39mm (without sleeve)
Product Weight	15grams
Load Bearing	500Kg
Recommended product location	Indoor or Outdoor
Lamp Supplied	Yes non-replaceable LED
Voltage (V)	230V
Maximum Lamp Wattage (W)	1Watts
Lumen Output	80Lm
Dimmable	No
Class	Class I. Must be Earthed
IP	IP65
Distance from lighted object	n/a
Photometric Testing	Not available
Instruction sheet	Yes
Origin of manufacture	China
Main materials:	
• Body	304 Stainless Steel
• Sleeve	Polycarbonate
• Glass	5mm Glass
• Reflector	N/A
Method of fix	With or without sleeve
Lamp type and base	1 x SMD LED
Electrical Connections	Direct fixed cable 1mtr (supplied)
Cable rating (mm SQ /C.S.A.) & type	3core 0.75mm H05RN-F
CE mark	Yes
Quality Assurance System	Yes ISO 9001 QMS
Batch coding details on product	Yes
Certificate of Conformity (Held on File)	Yes
Manufactured in accordance to:	EN60598
Warranty	1 year

ML Accessories Ltd. reserves the right to withdraw, improve or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.