

DATASHEET



VFRSHGICB / VFRSHGICC / VFRSHGICCBR / VFRSHGICW

230V IP65 Fire-Rated Downlight

www.mlaccessories.co.uk

MLA PART CODE	VFRSHGICB	VFRSHGICC	VFRSHGICCBR	VFRSHGICW
DESCRIPTION	IP65 IC Fire-Rated Shower Downlight			
FINISH	Brass	Chrome	Brushed Chrome	White
NETT WEIGHT (KG)	0.3			
DIMENSIONS (MM)	Diameter – 87 Recessed Depth – 118			
CUT-OUT (MM)	70			
MINIMUM VOID (MM)	175			
WATTAGE (W)	35			
LAMP BASE	GU10			
FIRE RATING (SOLID WOOD JOIST)	30/60/90 minutes			
INPUT VOLTAGE	230V 50Hz			
CONSTRUCTION	Pressed Steel / Aluminium			
IC RATED	Suitable for use with glass / mineral wool insulation only			
CLASS	Class I			
IP RATING	IP65 (IP20 from above)			
DIMMABLE	Dependent on lamp			
WARRANTY	1 year			
ORIGIN OF MANUFACTURE	China			
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes			
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598			
EAN	5055832915133	5055832915157	5055832915171	5055832915195



DCMAR21_V5

