

CAT7N7P5P415VAC

S+S CAT7N Starter DOL 7.5kW Start Stop 415VAC Control No Overload



DOL STARTERS

sprecher+schuh



Component type	Motor starter/Motor starter combination
Range	CAT7N
Model	N/A
Product status	Existing

The Sprecher+Schuh CAT7N range offers reliable DOL or full voltage motor starting for various motor sizes. Available in different operator cover controls and control voltage options, it ensures precise motor protection with CEP7-1 electronic overload relays. With a wide current adjustment range, only two parts cover 3.2 to 27A, reducing the number of stocked part numbers.

ELECTRICAL

Type of motor starter	Direct online starter (DOL)
Rated operation power at AC-3, 400 V	7.5 kW
Rated operation current at AC-3, 400 V	16 A
Rated operation current Ie	16 A
Voltage type for actuating	AC
Control supply voltage Us at AC 50HZ	415 V

CONSTRUCTION

Device construction	Enclosed
Material	Plastic
IP rating	IP66

DIMENSIONS

Depth	116.5 mm
Height	207.9 mm
Width	97.9 mm

RELATED PRODUCTS

ACCESSORY



Item No: CEP71EEAB

Required: No

Description: S+S CEP71 Overload Electronic Basic 0.1 to 0.5A for CA7 9 and 23A



Item No: CEP71EECB

Required: No

Description: S+S CEP71 Overload Electronic Basic 1.0 to 5.0A for CA7 9 and 23A



Item No: CEP71EEBB

Required: No

Description: S+S CEP71 Overload Electronic Basic 0.2 to 1.0A for CA7 9 and 23A



Item No: CEP71EEDB

Required: No

Description: S+S CEP71 Overload Electronic Basic 3.2 to 16A for CA7 9 and 23A

CAT7N7P5P415VAC

S+S CAT7N Starter DOL 7.5kW Start Stop 415VAC Control No Overload



DOL STARTERS

sprecher+schuh

RELATED PRODUCTS

ACCESSORY



Item No: CEP71EEEB

Required: No

Description: S+S CEP71 Overload Electronic Basic 5.4 to 27A for CA7 9 and 23A