



Representative Photo Only  
(actual product may vary based on configuration selections)

CSB flush mount loadcentre, 12way, transparent door

- IP40 rating
- Split neutral and earth bars rated 100A
- Removable earth and neutral bar
- White or transparent door
- Door hinged at the top
- Supplied complete with busbar comb
- Base (ABS)
- Door (white -ABS), (transparent (polycarbonate))
- 8way- Neutral split 4/4 & 8way earth, 12way- Neutral split 5/3/3 & 12way earth
- 18way- Neutral split 9/3/3/3 & 18way earth, 24way- Neutral split 10/3/3/3/3 & 24way earth
- 36way- Neutral split 12/12/12 & 36way earth

**SPECIFICATIONS**

|  |                                      |
|--|--------------------------------------|
| Product Series                                 | CSB                                  |
| Component Type Power Distribution & Protection | Loadcentre Enclosure                 |
| IP Rating                                      | IP40                                 |
| Number of Poles                                | 12                                   |
| MCB Type                                       | DIN Profile                          |
| Material, Body / Housing                       | ABS material                         |
| Colour, Body / Housing                         | White colour                         |
| Material, door                                 | White-ABS, Clear PC ( PolyCarbonate) |
| Colour, Door                                   | Clear / Transparent door             |
| Ue, rated operational voltage, AC, 3ph, nom    | 415 V AC                             |
| Ue, rated operational voltage, AC, 1ph, nom    | 240 V AC                             |
| In, Rated Current                              | 100 A                                |
| In, rated current, busbar comb, centre feed    | 130 A                                |
| In, rated current, busbar comb, end feed       | 80 A                                 |
| Tunnels, neutral bar                           | 5/3/3                                |
| Tunnels, earth bar                             | 12                                   |
| Mounting                                       | Flush Mount                          |
| Height   | 246 mm                               |
| Width  | 304 mm                               |
| Depth  | 95 mm                                |
| Height, base                                   | 211 mm                               |
| Width, base                                    | 270 mm                               |
| Depth, Base                                    | 66 mm                                |
| Height, cover                                  | 246 mm                               |
| Width, cover                                   | 304 mm                               |
| Depth, cover                                   | 29 mm                                |
| Height, Cutout                                 | 199 mm                               |
| Width, Cutout                                  | 259 mm                               |

# Catalogue No: **CSB12FT**

## LOADCENTRE 12 WAY DIN FLUSH TRANSPARENT DOOR

Power Distribution and Protection > Distribution Boards > Loadcentre Assemblies > MOD6 Range of Loadcentres > MOD6 CSB Loadcentres > Insulated Flush Mount Transparent Door



Earth and Neutral bar Rating 100 A 16 mm tunnel terminals

Standards Compliance AS/NZS 3439.3

### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -