

# DTM10140C

NHP DIN-T Miniature Circuit Breaker MCB 10kA 1 Pole 40A C Curve



<b>Component type</b>	Miniature circuit breaker (MCB)
<b>Range</b>	DIN-T MCB
<b>Model</b>	N/A
<b>Product status</b>	New Item

NHP DIN-T Miniature Circuit Breakers (MCB) are high-performance electrical protection devices offering a comprehensive range of features to meet the needs of any project. These MCBs are available in short circuit ratings of 6kA and 10kA with current ratings from 0.5A through to 125A in variety of B, C or D trip curves. These MCBs are available in 1P, 2P, 3P and 4P housings.

## ELECTRICAL

Rated current	40 A
Number of poles (total)	1
Trip curve	C
Rated voltage	240 V
Frequency	50-60 Hz
Voltage type	DC
Service voltage $U_b$ , AC	12 V
Service voltage $U_b$ , DC	12 V
Nominal operating voltage $U_n$ , DC	65 V
Rated short-circuit breaking capacity $I_{cn}$ according to AS/NZS 60898 at 230 VAC	10 kA
Rated short-circuit breaking capacity $I_{cn}$ according to AS/NZS 60898 at 400 VAC	10 kA
Rated short-circuit breaking capacity $I_{cu}$ according to AS/NZS 60947-2 at 230 VAC	15 kA
Rated short-circuit breaking capacity $I_{cu}$ according to AS/NZS 60947-2 at 400 VAC	15 kA
Max. rated operation voltage $U_e$	253 V
Rated insulation voltage $U_i$	440 V
Rated impulse withstand voltage $U_{imp}$	4 kV

## CONSTRUCTION

Number of protected poles	1
IP rating	IP40

## MECHANICAL

Connectable conductor cross section solid-core	0.75-35 mm <sup>2</sup>
Connectable conductor cross section multi-wired	0.75-35 mm <sup>2</sup>

## DIMENSIONS

Height	85 mm
Width	17.5 mm
Depth	75 mm

# DTM10140C

NHP DIN-T Miniature Circuit Breaker MCB 10kA 1 Pole 40A C Curve



<b>DIMENSIONS</b>	Width in number of modular spacings	1
	Weight	0.12 kg
<b>ENVIRONMENT</b>	Pollution degree	3
	Rated surrounding temperature without derating	30 °C
	Rated temperature	-25...55 °C