




General Information

Dimensions (mm)	555 (L) x 200 (W) x 100 (D)
Spigot Diameter (mm)	76
Materials	Body: Powdercoated Aluminium Diffuser: Glass
Finish	Light Grey (RAL 7037)
Product Weight (Kg)	3.66
Ingress Protection	IP66
Impact Rating (IK)	10
Warranty (Years)	5

Supply & Power Information

Input Voltage & Frequency (V~ / Hz)	100-277 50/60
Safety Class	I
Surge Protection Installed	Yes
Circuit Wattage (W)	20
LED Wattage (W)	20
Inrush Current	20A (44.8uS@230V~)
Power Factor	>0.9
Operating Temperature (°C)	-20 to +50
Maximum Critical Temperature (°C)	+90
Input Terminations	3 Pole Screw Terminals

Luminaire Output


Colour Temperature (K)	3000	4000	6000
Typical Luminous Flux (lm)	2800	3100	2800
Efficacy (lm/W)	140	155	140
Colour Rendering Index (CRI)	>70		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	50,000		

Dimming Information


Dimmable	No
----------	----

Compatible Accessories


OV113PC - 3 Pin IP65 Photocell
OV113WB - 1175mm Wall Bracket - Grey



3000



4000



6000

