


# INCEPTOR® MURUS

## Technical Specification

Product Code: OV2071LG25PC

Description: 25W LED Wall Pack - Standard With Photocell - IP66 - CTA - Light Grey



### General Information

Dimensions (mm)	267.4 (W) x 147 (D) x 332.6 (H)
Materials	Base & Cover: Powdercoated Aluminium Diffuser: Polycarbonate
Finish	Light Grey (RAL 7037)
Product Weight (Kg)	2.98
Ingress Protection	IP66
Impact Rating (IK)	10
Mounting	Wall
Warranty (Years)	5

### Supply & Power Information

Input Voltage & Frequency (V~ / Hz)	220-240 50
Safety Class	I
Surge Protection Installed	Yes
Circuit Wattage (W)	25
LED Wattage (W)	25
Input Current (mA)	0.109
Inrush Current	15A (183µS)
Power Factor	>0.9
Driver Information	Integrated (Tridonic)
Operating Temperature (°C)	-25 to +50
Maximum Critical Temperature (°C)	+80
Input Terminations	3 Pole Push-fit Terminals

### Luminaire Output


Colour Temperature (K)	3000	4000	6000
Typical Luminous Flux (lm)	2500	3000	2500
Efficacy (lm/W)	100	120	100
Beam Angle (°)	80 x 140		
Colour Rendering Index (CRI)	>80		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	50,000		

### Dimming Information


Dimmable	No
----------	----

### Sensor Information


Ambient Light 'On' (Lux)	10
Ambient Light 'OFF' (Lux)	20



3000



4000



6000



Ovia Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom

T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com