

General Information

Dimensions (mm)	595 (L) x 595 (W) x 66 (D)
Materials	Gear Tray: Powder Coated Steel; Diffuser: Polycarbonate; Back Panel: Powder Coated Steel
Colour	White (RAL9016)
Product Weight (Kg)	2.4
Ingress Protection	IP20
Impact Rating (IK)	06
Flammability Rating	TP(a)
Warranty (Years)	5

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50/60)
Safety Class	II
Circuit Wattage (W)	30
Input Current (mA)	140
Inrush Current	<40A (350uS@220V~)
Power Factor	>0.9
Driver Information	Remote Driver Supplied
Operating Temperature (°C)	-20 to +45
Maximum Critical Temperature (°C)	+80
Prewired Flow™ Connector	3 Pole CT105-F Push-fit Terminals

Luminaire Output

Colour Temperature (K)	3000	4000	6000
Typical Luminous Flux (lm)	3200	3300	3300
Efficacy (lm/W)	106	110	110
Beam Angle (°)	120		
Colour Rendering Index (CRI)	>80		
Flicker Free	Yes		
LED Lifetime (L70) (Hours)	30000		

Dimming Information


Dimmable	No
----------	----

Compatible Accessories


- OVCGMF0001 - 240V~ 29-48W Multi-function Dimmable Constant Current LED Driver
- OVSUSP731 - Suspension Wire Kit
- OVREC731 - 600mm x 600mm Recess Frame Kit
- OEP4 - 3 Hour Emergency Pack
- OEP4-ST - 3 Hour Self-Test Emergency Pack

Additional Information


- Suspension hooks pre-fitted to the back



Corridor



Corridor Wide



Open Area



OVIA Limited, Scolmore House, Mariner, Lichfield Road Industrial Estate,
 Tamworth, Staffordshire, B79 7UL United Kingdom
 T: +44 (0)1827 300640
 E: sales@oviaUK.com | W: oviaUK.com



Catalogue



Section



DoC



Installation

