

# Metal Detectable Cable Ties and Mounts

## Ordering Information

### Nylon Metal Detectable Products

- Excellent solution for general purpose maintenance and repair applications
- Ideal for use in control panels and overhead cable runs




### Cable Ties

Part Number	Length In. (mm)	Width In. (mm)	Thickness In. (mm)	Head Height In. (mm)	Head Width In. (mm)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength Lbs. (N)	Recommended Tools	Std. Pkg. Qty.*
<b>Miniature Cross Section</b>									
PLT1M-C86	3.9 (100)	0.098 (2.5)	0.044 (1.1)	0.186 (4.8)	0.188 (4.8)	0.87 (22)	18 (80)	GTS-E, GS2B-E	100
<b>Intermediate Cross Section</b>									
PLT2I-C86	8.0 (203)	0.135 (3.4)	0.047 (1.2)	0.180 (4.6)	0.240 (6.1)	2.00 (51)	30 (133)	GTS-E, GS2B-E	100
<b>Standard Cross Section</b>									
PLT2S-C86	7.3 (186)	0.190 (4.8)	0.057 (1.4)	0.240 (6.1)	0.320 (8.1)	1.85 (47)	50 (222)	GTS-E, GS2B-E, GTH-E, GS4H-E	100
PLT3S-C86	11.5 (291)					3.00 (76)			100
PLT4S-C86	14.4 (366)					4.00 (102)			100
<b>Light-Heavy Cross Section (Straight Tip)</b>									
PLT3H-L86	11.1 (282)	0.300 (7.6)	0.075 (1.9)	0.360 (9.1)	0.480 (12.2)	3.00 (76)	120 (534)	GTH-E, GS4H-E	50
PLT4H-L86	14.4 (366)					4.00 (102)			50

### Cable Tie Mounts

Part Number	Used With Cable Ties	A Width In. (mm)	B Length In. (mm)	C Height In. (mm)	Counterbore Diameter In. (mm)	Mounting Method	Std. Pkg. Qty.*
TM2S8-C86	Min., Int., Std.	0.630 (16.0)	0.422 (10.7)	0.275 (7.0)	0.325 (8.3)	#8 (M4) screw	100
TM3S8-C86	Std.,	0.867 (22.0)	0.614 (15.6)	0.373 (9.5)	0.325 (8.3)	#8 (M4) screw	100
TM3S10-C86	Lt. Hvy.				0.385 (9.8)	#10 (M5) screw	100



\*Order number of pieces required in multiples of standard package quantity.

### Quality Assurance

All cable tie and mount packages contain a quality control number for complete product traceability; each lot passes metal detection as part of final product verification.