



CorePro GLASS LED candles and lustres

CorePro LEDCandleND2-25W ST35 E14 827CLG

Featuring a classic heritage design, these filament LED candles combine the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb is a very easy choice for people who are looking for a retrofit LED replacement, it provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

Product data

General Information	
Cap base	E14 [E14]
Nominal lifetime	15,000 h
Switching Cycle	20,000
Lighting Technology	LED
Flux measurement reference	Sphere
CE mark	Yes
EU RoHS compliant	Yes

Light Technical	
Colour Code	827 [CCT of 2700K]
Luminous Flux	250 lm
Colour designation	Warm White (WW)
Correlated Colour Temperature	2700 K
Luminous efficacy (rated) (nom.)	125.00 lm/W
Colour consistency	<6
Colour rendering index (CRI)	80
LLMF at end of nominal lifetime (nom.)	70 %

Flickering value (PstLM)	1
Stroboscopic effect	0.4
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input frequency	50 to 60 Hz
Power Consumption	2 W
Lamp current (nom.)	20 mA
Wattage equivalent	25 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.4
Voltage (nom.)	220-240 V

Temperature	
T-Case maximum (nom.)	36 °C

CorePro GLASS LED candles and lustres

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Lamp Finish	Clear
Bulb shape	ST35


Approval and Application

Energy Efficiency Class	E
Energy-saving product	Yes
Suitable for accent lighting	No
Energy consumption kWh/1,000 hours	2 kWh
EPREL registration number	387362
EyeComfort	Yes

Product Data



Order product name	CorePro LEDCandleND2-25W ST35 E14 827CLG
Full product name	CorePro LEDCandleND2-25W ST35 E14 827CLG
Full EOC	871951434772400
Order code	34772400
Material no. (12 NC)	929001238592
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8719514347724
Numerator – packs per outer box	10
EAN/UPC – Case	8719514347731

Dimensional drawing



Product	D	C
CorePro LEDCandleND2-25W ST35 E14 827CLG	35 mm	97 mm

Photometric data




Spectral Power Distribution Colour - CorePro LEDCandleND2-25W ST35 E14 827CLG

General uniform lighting - CorePro LEDCandleND2-25W ST35 E14 827CLG

CorePro GLASS LED candles and lustres

Photometric data



Light Distribution Diagram - CorePro LEDCandleND2-25W ST35 E14 827CLG

Lifetime



Life Expectancy Diagram - CorePro LEDCandleND2-25W ST35 E14 827CLG



Lumen Maintenance Diagram - CorePro LEDCandleND2-25W ST35 E14 827CLG

