



Description:
20A 2 Pole 230V 1 Module Normally Closed Contactor



- Features:**
- Provides a method of remotely switching single and three phase loads
 - Ideal for switching heating, lighting and ventilation circuits
 - Use in conjunction with REC supply off-peak tariffs
 - Suitable for mounting on a standard DIN rail
 - Fully compatible with Prote

Technical:	
Height	86mm
Width	18mm
Depth	68mm
Weight	0.120 Kg
Guarantee	12 Months
Frequency	50 Hz
Current rating	20A
Rated operated voltage	230V ac.
Number of modules	1
Packaging types	Each
Product range	Contactors
Standards	BS EN 60947-4-1
Protection class ip rating	IP2X
Compliance	Electromagnetic Compatibility Directive 2014/30/EU
Intended use	Din mounted contactor for switching 230/415v AC loads
Manufacturer	Proteus Switchgear. Pipers Road. Redditch. Worcestershire. B98 0HU. United Kingdom.

DECLARATION of CONFORMITY

Product Code:

CT202NC

Description:

20A 2 Pole 230V 1 Module Normally Closed Contactor



Intended Use:

Din mounted contactor for switching 230/415v AC loads

Manufacturer:

Proteus Switchgear. Pipers Road. Redditch.
Worcestershire. B98 0HU. United Kingdom.

Ratings & Characteristics:

Voltage Rating	230V ac.
Current Rating	20A
Frequency	50 Hz

Compliance:

Electromagnetic Compatibility Directive
2014/30/EU, Low Voltage Directive 2014/35/EU,
Restriction of the use of certain hazardous
substances directive 2011/65/EU, Waste Electrical
and Electronic Equipment directive 2012/19/EU

Designated Standards:

BS EN 60947-4-1



I declare that the object of the declaration above is in conformity with the relevant harmonization legislation and national standards.

Signed for and on behalf of Proteus Switchgear

Date:

27/02/2024



Kieran Jenkins.
Senior Works Manager.