

Product Code:

U125FS4P

Product Range:

 4 Pole, Switch & Switch Fuse
 Disconnectors, Switch Disconnector Fuses, U
 Range, U Ranges Switch Fuses

Issue Date:

20/02/2025

Description:

 125A Four Pole Metalclad Switch Disconnector Fuse
 complete with Fuses fitted

Features:

- This range of wall mounting switch disconnector fuses are rated from 63A to 630A Three Pole and Neutral, Four pole configuration available upon request
- Switch mechanism rated at 65kA when fitted with appropriate BS88 fuses, Fully rated BS88 fuses fitted
- Designed to meet the requirements of industrial and commercial installations
- Heavy duty interlocking handle, Padlockable in off position for security
- Screened cable terminations
- Epoxy powder coat finish
- Robust, heavy duty steel enclosure
- Folded steel construction for extra rigidity
- Flush fitting door, removable for ease of installation
- Built-in cable box suitable for most applications
- Manufactured to BSEN60947 parts 1 & 3

Technical:

Height	500 mm
Width	350 mm
Depth	185 mm
Weight	11.89 Kg
Short circuit rating	65kA
Torque	20Nm
Ambient temperature	-5 to +40 C
Mounting	Wall Mounted
Guarantee	12 Months
Frequency	50 Hz
Cable entry	Top And Bottom Glandplates Removable For Ease Of Cutting
Current rating	125A
Rated operated voltage	230/400V ac.
Incoming terminal capacity	M8 Bolts 70mm Square Cable (When using 95mm cable it is recommended that the UCB1 is fitted)
Packaging types	Each
Product range	Switch Disconnector Fuse
Standards	BS EN 60947-3
Protection class ip rating	IP3X
Fuse type	PDD125
Enclosure	1.2mm Cold rolled steel with an epoxy paint finish to RAL7035 matt grey.
Door covers	Screw fixed hinged interlocked door.
Compliance	Low Voltage Directive 2014/35/EU
Intended use	A range of switch disconnector fuses and switch

Proteus Switchgear Website:

www.proteusswitchgear.co.uk

disconnectors which are rated for on-load switching
and provide isolation of the switched circuit.

Manufacturer

Proteus Switchgear. Stafford Park 12. Telford.
Shropshire. TF3 3BJ. United Kingdom.

DECLARATION of CONFORMITY

Product Code:

U125FS4P

Description:

125A Four Pole Metalclad Switch Disconnecter Fuse complete with Fuses fitted



Intended Use:

A range of switch disconnecter fuses and switch disconnectors which are rated for on-load switching and provide isolation of the switched circuit.

Manufacturer:

Proteus Switchgear. Stafford Park 12. Telford. Shropshire. TF3 3BJ. United Kingdom.

Ratings & Characteristics:

Voltage Rating	230/400V ac.
Current Rating	125A
Frequency	50 Hz

Compliance:

Low Voltage Directive 2014/35/EU, Restriction of the use of certain hazardous substances directive 2011/65/EU, Waste Electrical and Electronic Equipment directive 2012/19/EU

Designated Standards:

BS EN 60947-3



I declare that the object of the declaration above is in conformity with the relevant harmonization legislation and national standards.

Signed for and on behalf of Proteus Switchgear



Date:
20/02/2025