

Switch Disconnect



U100S


General Duty

Current Rating A	CSA Max mm ²	Bolt Size (metric)	Power rating at 400V (kW)	Cat. No.	H (mm)	W (mm)	D1 (mm)	D2 (mm)
63	95*	M8	33	U63S	504	355	185	70
100	95*	M8	55	U100S	504	355	185	70
125	95*	M8	59	U125S	504	355	185	70
160	95*	M8	75	U160S	504	355	185	70
200	150/185**	M10	110	U200S	705	410	255	70
250	150/185**	M10	132	U250S	705	410	255	70
315	185**	M10	185	U315S	705	410	255	70
400	185/240#	M10	220	U400S	905	410	330	70
500	-	M12	275	U500S	1330	510	300	70
630	-	M12	300	U630S	1330	510	300	70

* - when using 95mm² cable it is recommended that the UCB1 is fitted.

** - when using 185mm² cable it is recommended that the UCB2 is fitted.

- when using 240mm² cable it is recommended that the UCB4 is fitted.



UCB2

Accessories

Description	Cat. No.	H (mm)	W (mm)	D (mm)
Cable spreader box to suit up to U160FS/ U160S	UCB1	200	355	185
Cable spreader box to suit U200FS/U200S upto U315FS/U315S	UCB2	200	410	255
Cable spreader box to suit U400FS/U400S	UCB4	200	410	330
Cable spreader box for 630FS (12")	2CB12	305	485	145
Cable spreader box for 630FS (15")	2CB15	385	485	145