

Product Code:

Description:

# CCP c/w Flex 6Amp Clip-in-Ceiling Plug c/w Flex

**LinkFast** LDS



Part Code:	Description:
CCP2-0.75	- 3 Pin plug - 2Mtrs x 0.75mm <sup>2</sup> Flex
CCP3-0.75	- 3 Pin plug - 3Mtrs x 0.75mm <sup>2</sup> Flex
CCP2-1	- 3 Pin plug - 2Mtrs x 1mm <sup>2</sup> Flex
CCP3-1	- 3 Pin plug - 3Mtrs x 1mm <sup>2</sup> Flex
CCP2-0.75LSF	- 3 Pin plug - 2Mtrs x 0.75mm <sup>2</sup> Low SmokeFlex
CCP3-0.75LSF	- 3 Pin plug - 3Mtrs x 0.75mm <sup>2</sup> Low Smoke Flex
CCP2-1LSF	- 3 Pin plug - 2Mtrs x 1mm <sup>2</sup> Low Smoke Flex
CCP3-1LSF	- 3 Pin plug - 3Mtrs x 1mm <sup>2</sup> Low Smoke Flex

Compliance:	BS 6972: 1988 CE Compliant: 93/68/EEC BS 5733: 1995 BS 6500
Flex:	- Standard Flex: 318Y Cable HO5VV-F - Low Smoke Zero Halogen: 318B LSZH Cable HO5Z1Z1-F
Material:	Polycarbonate
Load:	5kg Static Suspended Load
Current:	6Amps
Voltage:	230 - 250V a.c.
Frequency:	50Hz
Box Quantity:	5 pieces / 0.96Kgs(CCP3-0.75)/ 0.0039M <sup>3</sup>
Environmental Issues:	<i>Packaging Waste:</i> Cardboard - 0.0013Kg / 125T/125T B Flute Inner bag - 0.0009Kg / LDPE#4 RoHS Compliant - ref: 2002/95/EC The products manufactured & otherwise supplied by the company do not have any perceived or known hazardous materials or by-products that would be deemed hazardous to the environment.