



DIM 550DP/NR - 23W 350/550mA

Australian approved dimmable constant current LED driver with selectable power.

Application

The perfect choice for constant current electronic lighting circuits

Design Specifications

- Compact design, SELV, electrical class II, EMC compliant
- Safe no load, overload, short circuit protection
- Onboard selectable output current 350/550mA
- Dimmable with a trailing edge dimmer, delivering flickerCONTROLLED driver performance.
- Recommended SAL trailing edge dimmers SDD400U, SDA450U/LED, SDD350UM, SDD300BTAM
- Electrical class II, Do Not Cover



Performance

- Dimmable - **YES**
- Dimmer Type - **TRAILING EDGE**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Frequency (Hz)	Output Current (mA)	Power (W)	Power Factor
	DIM550/23DP/NR	240	50	550	23	0.9

Dimmable	Dim (mm)
YES	140(L) x 42(W) x 29(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

Wiring Diagram

