



UNIFIT S9053TCP2 - 10W

Dimmable 10 watt LED module, with selectable CCT

Application

Ideal for any residential or commercial interior space

Design Specifications

- Efficient die-cast aluminium heat sink
- High performance LED optics
- Multi-faceted reflector system, 60° beam distribution
- Polycarbonate optical lens
- Remote, trailing edge dimmable LED driver, fitted with flex and plug
- A comprehensive range of downlight trims are available, see MIX & MATCH model numbers
- Double insulated








Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, optional 1-10V, DALI / DSI**






Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9053TCP2	240	10	750/900/850	3000/4000/5700	60
	S9008TC2WH	240	10	750/900/850	3000/4000/5700	60
	S9008TC2BK	240	10	750/900/850	3000/4000/5700	60
	S9009TC2WH	240	10	750/900/850	3000/4000/5700	60
	S9009TC2BK	240	10	750/900/850	3000/4000/5700	60
	S9011TC2WH	240	10	750/900/850	3000/4000/5700	60
	S9011TC2BK	240	10	750/900/850	3000/4000/5700	60

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80			50	50(H)
YES	80	MATT WHITE	76	82	80(H)
YES	80	MATT BLACK	76	82	80(H)
YES	80	MATT WHITE	76	82	80(H)
YES	80	MATT BLACK	76	82	80(H)
YES	80	MATT WHITE	92	102	95(H)
YES	80	MATT BLACK	92	102	95(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



S9053TCP2 LED module

MIX AND MATCH THE TRIM PROFILES

