



## CLARE S9062TC/S - 10W

Recessed LED downlight with PIR sensor control and selectable CCT

### Application

Ideal for interior service areas, bathrooms and storage spaces

### Design Specifications

- Selectable CCT 3000K / 4000K / 5700K
- Integral PIR sensor control with a fixed 90 seconds ON motion detection function incorporating a light sensor function to engage when the lighting levels are <20lux
- Integral non-dimmable LED 10 watt control gear, IC - 4 rated, complete with flex & plug
- Stylish white trim with an opal PC diffuser
- Double insulated
- Cut - out 92mm



### Performance

- In Built Sensor - **YES**
- Sensor Type - **PIR**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9062TC/S	240	10	760/800/850	3000/4000/5700	90


CRI	Body Colour	Cut Out (mm)	Dim (mm)
80	WHITE	92	115(W) x 73(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



## Dimensions

S9062TC-S CUT - OUT 92mm



Model No.	Input (V)(V)	Power (W)	Lumens (lm)	Life Current (A)	Is-on-h Current (A)	CR	CCT (K)	Beam Colour (°W, °g)	Beam	Mass (kg)	Dimension (mm)
S9062TC-S	240/230	10	760 / 807 / 850	0.06	141A/100A-8/400µA	>=80	3000/4000/5000	White	0.2	Φ115 x H75	
Power (W)	Input (V)(V)	Detection Distance (m)	Detection Motion Speed (m/s)	Detection Angle	Working Humidity (RH)	Time Setting (s)	Light Control (lux)	Installation Height (m)	Sensor Type		
10	240/230	4.0/3.0/2.0	0.1/0.2/0.3	120°	0-90%	1-10/1/1.5	0-500	1.5-2	PIR		

\* It will turn off in 15 seconds if there is no motion detected.

## Photometric Data

Unit: cd C0/C180 — C90/C270 —

S9062TC/S at 3000K

