



UFO SHB23MPTC2 - 150/200W

1-10V Dimmable, IP65 LED super low profile LED highbay, with selectable power, CCT and 200lm/W performance

Application

Ideal for any commercial or industrial interior spaces

Design Specifications

- Black powder coated finish, die-cast aluminium body, super low profile design
- Dimmable 1-10V, selectable power 90/120/150W and 120/160/200W with selectable CCT 3000/4000/5000K
- High efficiency LED optics, clear polycarbonate lens, 90° beam distribution, SDCM <5, 200lm/W performance @ 4000K
- Optional plug and play motion and daylight harvesting sensor available, with remote control functions
- Integral 1-10V dimmable LED driver with surge protection, complete with flex and plug for easy installation
- Robust design IP65 and IK08 rated, stainless safety lanyard included











Performance

- Dimmable - **YES**
- Dimmer Type - **1-10V, optional SAL DALI (1) addressable signal converter**
- In Built Sensor - **OPTIONAL**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Multiple Wattage	Lumens (lm)	Beam Angle (°)
	SHB23MP150TC2	240	150	90/120/150	27500/30000/28300	90
	SHB23MP200TC2	240	200	120/160/200	36000/40000/37200	90
	SHB23SE/PLB					
	SHB23SE/PMR					
	SHB23SE/PPR					
	SHB2X/CS					
	LM-DALI010B					
	SHB2XS/RC					

CCT (K)	CRI	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)
3000/4000/5000	70	BLACK	280	170(H)	2
3000/4000/5000	70	BLACK	320	165(H)	2.32
		BLACK			0.26
		SILVER	500	236(H)	0.28
		CLEAR PC	480	250(H)	0.4
		WHITE			0.04
		DALI SIGNAL CONVERTER			0.06
		WHITE			0.14



NOTE: Lumens shown are at maximum power selection - **150TC2** (90) 17300/18000/17800lm, (120) 22300, 24000, 22800lm, (150) 27500, 30000, 28300lm - **200TC2** (120) 23000, 24000, 23800lm (160) 30000, 32000, 30600lm (200) 36000, 40000, 37200lm

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





Dimensions


150W





200W



SHB23SEPMR



SHBSEPPR



SHB23SE/PLB

