



DISC DIMMABLE SL2105TC - 30W

Dimmable IP54 LED Oyster 30 watt, with selectable CCT

Application

A perfect choice for apartments, residential or commercial spaces

Design Specifications

- Robust white polycarbonate body profile
- Quality opal polycarbonate diffuser
- High efficiency LED optics, CRI > 80, selectable CCT 3000K, 4000K or 5700K
- Dimmable IP54 LED Oyster 30 watt, with selectable CCT
- Low profile design, IP54, designed for weather protected (under eaves) installations, double insulated, ceiling mount



Performance

- Dimmable - YES
- Dimmer Type - **Compatible trailing edge dimmers, SDA450U, SDD400U**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SL2105/20TC	240	12	1100/1200/1200	3000/4000/5700	80
	SL2105/30TC	240	25	2450/2600/2500	3000/4000/5700	80
	SL2105/40TC	240	30	2800/3480/3000	3000/4000/5700	80




Beam Angle (°)	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)
120	WHITE	200	48(H)	0.42
120	WHITE	300	40(H)	0.8
120	WHITE	400	52(H)	1.4

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Photometric Data

Unit: cd C0/C180 — C90/C270 —

SL2105/20TC at 3000K



SL2105/40TC at 5700K

