



BOLLARD DOME SL7088DC TC - 10W

Dome profile, IP65 circular bollard, integral LED control gear with selectable CCT

Application

Ideal for residential or apartment exterior pathways

Design Specifications

- Die-cast aluminium body, dome profile design, base plate mounting, rag bolts included
- Durable BLACK powder coated finish
- Clear polycarbonate lens
- High efficiency LED optics
- Integral LED control gear, IP65, IK08 performance
- SL7088DC50TC - 120mm Ø, 670mm height
- SL7088DC85TC - 120mm Ø, 1020mm height



Performance

- Dimmable - NO



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)
	SL7088DC50TC/BK	240	10	725/760/740	3000/4000/5000	250
	SL7088DC85TC/BK	240	10	725/760/740	3000/4000/5000	250

Mass (kg)	Diameter (mm)	Dim (mm)	Body Colour
2.2	120	670(H)	BLACK
2.8	120	1020(H)	BLACK

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".