



## BLADE SL9707TC - 20W/35W


LED low profile batten with selectable CCT

### Application

Conventional LED profile battens for commercial service spaces

### Design Specifications

- Selectable CCT 3000K / 4000K / 5700K
- Extruded aluminium body with plastic end cap with a rear cable channel allowing easy wiring
- White powder coat finish
- Integral constant current non-dimmable LED driver, 20, 30 or 35 watt
- Robust opal polycarbonate diffuser
- High efficiency LED optics, CRI >80, 120° beam distribution



### Performance

- Dimmable - **NO**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SL9707/60TC	240	20	2500/2700/2600	3000/4000/5700	80
	SL9707/120TC	240	30	3800/4100/4000	3000/4000/5700	80
	SL9707/150TC	240	35	4500/4800/4700	3000/4000/5700	80



Beam Angle (°)	Dim (mm)	Body Colour	IPART
120	597(L) x 80(W) x 35(H)	WHITE	N/A
120	1197(L) x 80(W) x 35(H)	WHITE	N/A
120	1485(L) x 80(W) x 35(H)	WHITE	

**IMPORTANT**, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".