



## KEW II SL9721TC/MP/EM- 20/40W

MAINTAINED OR NON-MAINTAINED, LED emergency weatherproof batten, IP65 LED 20/40 watt with selectable power and CCT

### Application

Multi-purpose ceiling mount or suspended, commercial or industrial applications

### Design Specifications

- Vandal resistant design, robust polycarbonate body and UV stabilized polycarbonate diffuser
- 301 Stainless steel clips & screws, IP65, IK08, sensor and emergency options
- Operating temperature 0°C to +40°C
- Compliant to AS/NZS2293 Emergency Lighting & Exit Signs, guaranteed minimum 90 minutes emergency mode function with LiFePO4 battery technology
- Integral, non-dimmable flickerCONTROLLED LED driver
- Selectable power choices; 20W - 11/14/17/20 and 40W - 22/28/34/40
- Emergency spacing classification - (SL9721/20EM) D63@C0, D40@C90, (SL9721/35EM) D63@C0, D40@C90.





### Performance

- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



## Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	CCT (K)	Lumens (lm)	Multiple Wattage
	SL9721/20TC/MP/EM	240	20	3000/4000/5700	2550/2550/2500	11/14/17/20
	SL9721/40TC/MP/EM	240	40	3000/4000/5700	5050/5250/5400	22/28/34/40

Body Colour	Dim (mm)
GREY	618(L) x 116(W) x 74(H)
GREY	1215(L) x 116(W) x 74(H)

NOTE; Lumens (lm) display are at full maintained power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".