



KEW II SL9721TC/MP - 20/40W


IP65 LED weatherproof batten 20/40 watt with selectable power and CCT

Application

Multi-purpose ceiling mount or suspended, commercial or industrial applications

Design Specifications

- Vandal resistant design, robust polycarbonate body and UV stabilized polycarbonate diffuser
- 301 Stainless steel clips & screws, IP65, IK08, sensor and emergency options
- Operating temperature -20°C to +40°C
- Integral, non-dimmable flickerCONTROLLED LED driver
- Selectable power choices; 20W - 11/14/17/20 and 40W - 22/28/34/40
- Optional corridorSTANDBY functions available
Product selections compliant to AS/NZS2293
Emergency Lighting & Exit Signs are located in the [interior](#) and [exterior](#) emergency sections of this web catalogue



Performance

- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Multiple Wattage	Lumens (lm)	CRI
	SL9721/20TC/MP	240	20	11/14/17/20	2550/2550/2500	90
	SL9721/40TC/MP	240	40	22/28/34/40	5050/5250/5400	80



CCT (K)	Beam Angle (°)	Body Colour	Dim (mm)
3000/4000/5700	120	GREY	618(L) x 116(W) x 74(H)
3000/4000/5700	120	GREY	1215(L) x 116(W) x 74(H)

NOTE; Lumens (lm) display are at full power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".