



BARRACUDA SL9723TC/MP - 12/40W

IP66 LED vandal-proof batten, with selectable CCT and power

Application

Commercial or industrial ceiling or suspended mount applications requiring IP66 and IK10 performance

Design Specifications

- Selectable CCT 3000K /4000K /5700K
- Rounded profile design, robust aluminium body and UV stabilized polycarbonate diffuser.
- Integral non-dimmable, multi-power LED driver, 12/21 or 24/40 watt models
- Secure stainless steel fasteners for the diffuser retention, optional accessories - M6 304 stainless steel security screws to fit a T30 TORX key (SL9723TP/SCREW)
- Installation types - (via multiple end or rear conduit access points) Surface mount (standard), or Suspended (two off, SSY1512 wire suspension kits are required).
- Optional emergency models available






Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **DALI**





Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CRI	CCT (K)
	SL9723/20TC/MP	240	12/15/18/21	2300/2500/2400	80	3000/4000/5700
	SL9723/40TC/MP	240	24/30/35/40	4600/5000/4800	80	3000/4000/5700
	SL9723TP/SCREW					

Beam Angle (°)	Body Colour	Dim (mm)
120	GREY	698(L) x 137(W) x 115(H)
120	GREY	1306(L) x 137(W) x 115(H)
	M6 304 STAINLESS STEEL	137(W)

Lumens (lm) shown are displayed at FULL power, for switched lumen values, refer installation instructions

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".