



## OPAL SO3700/TC/DP2 - 8/30W

LED Oyster 8 to 30 watt, with selectable CCT, dual power and optional DALI<sup>2</sup>

### Application

A perfect choice for apartments or commercial spaces

### Design Specifications

- Selectable CCT 3000K / 4000K / 6000K
- Durable powder coated steel body profile with a high performance opal PMMA diffuser
- High efficiency LED optics, CRI > 80
- Integral, non-dimmable LED driver with dual power selections and optional DALI<sup>2</sup>
- Ceiling mount, two versatile profile sizes Ø 320 or 400mm



### Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge or DALI<sup>2</sup>**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE 40TC ONLY**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Power (W)	Lumens (lm)	CCT (K)
	SO3700/30TC/DP2	240	8/16		1100/1400/1200	3000/4000/6000
	SO3700/40TC/DP2	240	15/30		2350/2800/2400	3000/4000/6000
	SO3700/40TC/DALI	240		30	2600/2900/2690	3000/4000/6000



CRI	Dimmable	Beam Angle (°)	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)
80	NO	120	White	310	78(H)	0.54
80	NO	120	White	390	102(H)	0.86
90	YES	120	White	390	102(H)	0.88

IPART						
YES						
YES						
N/A						

Note 1: Lumens (lm) values shown are at full power rating

Note 2: Sensor SMS830 can be used for ON/OFF control only with SO3700/40TC/DP2 (non-dimmable).

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".