# Product data sheet
## Characteristics

# 15335
## Acti 9 - IH - mechanical time switch - 24 h - without memory



## Main

| | |
|---|---|
| Range of product | Acti 9 |
| Range | Acti 9 |
| Product name | Acti 9 IH |
| Device short name | IH |
| Product or component-type | Mechanical time switch |
| Number of channels | 1 |
| Function available | Manual time changeover |

## Complementary

| | |
|---|---|
| Device application | Building |
| Load type | 10 parallel-corrected fluorescent tube, ( 58 W )<br>15 parallel-corrected fluorescent tube, ( 40 W )<br>230 V AC halogen lamp, ( 1000 W )<br>230 V AC incandescent lamp, ( 1000 W )<br>3 parallel-corrected fluorescent tube, ( 100 W )<br>7 fluocompact lamp, ( 11 W )<br>7 fluocompact lamp, ( 15 W )<br>7 fluocompact lamp, ( 20 W )<br>7 fluocompact lamp, ( 7 W ) |
| Cycle duration | 24 h |
| Measurement accuracy | +/- 1 s/day |
| Maximum number of switchings | 48 on - 48 off |
| Minimum interval duration | 15 min |
| Type of setting | Manual time changeover |
| Measurement accuracy | +/- 1 s/day 20 °C |
| Power consumption in VA | 2.5 VA |
| Maximum switching current | 16 A - 250 V AC pf = 1<br>4 A - 250 V AC pf = 0.6 |
| [Ue] rated operational voltage | ( +/- 10 % ) 230 V AC 50/60 Hz |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Colour tint | White (RAL 9003) |
| Connections - terminals | Screw terminals |
| IP degree of protection | IP20 B |
| Width | 18 mm |
| Height | 90 mm |
| Depth | 66 mm |
| Product weight | 0.097 kg |
| Function | None |
| Absence for holidays | No |
| Time changeover | Manual |
| Updated by | None |
| Compatibility code | IH |
| Market segment | Residential<br>Small commercial |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

| | |
|---|---|
| Ambient air temperature for operation | -10...50 °C |
| IP degree of protection | Terminals : IP20 B |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0625 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACh | Reference contains SVHC above the threshold - Go to CaP for more details- Go to CaP for more details |
| Product environmental profile | Available |
| Product end of life instructions | Available |

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |

Product Life Status : Commercialised