

# Product datasheet

Specifications



Switch disconnecter, ComPact, Compact INS250-160, 160 A, standard version with black rotary handle, 3 poles

31104

## Main

Range	ComPact
Product or component type	Switch disconnecter
Product name	ComPacT INS
Poles description	3P
Network type	DC AC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-22A: 160 A AC 50/60 Hz 220/240 V AC-22A: 160 A AC 50/60 Hz 380/415 V AC-22A: 160 A AC 50/60 Hz 440/480 V AC-22A: 160 A AC 50/60 Hz 480 V NEMA AC-22A: 160 A AC 50/60 Hz 500/525 V AC-22A: 160 A AC 50/60 Hz 660/690 V AC-23A: 160 A AC 50/60 Hz 220/240 V AC-23A: 160 A AC 50/60 Hz 380/415 V AC-23A: 160 A AC 50/60 Hz 440/480 V AC-23A: 160 A AC 50/60 Hz 480 V NEMA AC-23A: 160 A AC 50/60 Hz 500/525 V AC-23A: 160 A AC 50/60 Hz 660/690 V DC-22A: 160 A DC 125 V 2 poles in series DC-23A: 160 A DC 125 V 2 poles in series
[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Ith] conventional free air thermal current	160 A at 60 °C
[Icm] rated short-circuit making capacity	30 kA switch-disconnector alone 690 V AC at 50/60 Hz 330 kA with upstream protection circuit breaker 690 V AC at 50/60 Hz
[Ue] rated operational voltage	125 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

## Complementary

Control type	Direct front rotary handle
Handle colour	Black
Mounting mode	Fixed
Mounting support	Plate Rail
Upside connection	Front

<b>Downside connection</b>	Front
<b>Maximum power</b>	AC-23: 110 kW at 500/525 V AC 50/60 Hz AC-23: 45 kW at 220/240 V AC 50/60 Hz AC-23: 45 kW at 230 V AC 50/60 Hz (NEMA) AC-23: 75 kW at 380/415 V AC 50/60 Hz AC-23: 90 kW at 440 V AC 50/60 Hz AC-23: 90 kW at 480 V AC 50/60 Hz (NEMA) AC-23: 90 kW at 660/690 V AC 50/60 Hz
<b>Rated duty</b>	Uninterrupted
<b>[I<sub>cw</sub>] rated short-time withstand current</b>	1.8 kA during 30 s conforming to IEC 60947-3 2.2 kA during 20 s conforming to IEC 60947-3 4.9 kA during 3 s conforming to IEC 60947-3 8.5 kA during 1 s conforming to IEC 60947-3
<b>Mechanical durability</b>	15000 cycles
<b>Electrical durability</b>	AC-22A: 1500 cycles 440 V AC 50/60 Hz AC-22A: 1500 cycles 500 V AC 50/60 Hz AC-22A: 1500 cycles 690 V AC 50/60 Hz AC-23A: 1500 cycles 440 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 690 V AC 50/60 Hz DC-22A: 1500 cycles 125 V DC 2 poles in series DC-23A: 1500 cycles 125 V DC 2 poles in series
<b>Connection pitch</b>	35 mm
<b>Height</b>	136 mm
<b>Width</b>	140 mm
<b>Depth</b>	96 mm
<b>Net weight</b>	2 kg

## Environment

<b>Standards</b>	IEC 60947-1 IEC 60947-3
<b>Product certifications</b>	CCC KEMA-KEUR
<b>IP degree of protection</b>	IP40 conforming to IEC 60529
<b>IK degree of protection</b>	IK07 conforming to EN 50102
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-50...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	17.000 cm
<b>Package 1 Width</b>	14.000 cm
<b>Package 1 Length</b>	15.900 cm
<b>Package 1 Weight</b>	2.000 kg
<b>Unit Type of Package 2</b>	S04
<b>Number of Units in Package 2</b>	9
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	40.000 cm
<b>Package 2 Length</b>	60.000 cm

---

Package 2 Weight 20.893 kg

## Contractual warranty

---

Warranty 18 months



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint 155

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number E07f84b1-8f0b-4216-b13d-b812d80ed78b

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Technical Illustration

Assembly's dimensions

---

