

Product data sheet

Specifications

SQUARE D



Foot Switch, Harmony 9002AW, industrial, oversized pedal and safety and side shields, SPDT contact, NEMA 4, 13, two stage, 5A at 600V AC

9002AW117

Product availability: Stock - Normally stocked in distribution facility

Price*: 750.00 USD

Main

| | |
|-------------------------|---|
| Range | 9002AW |
| Product | Foot switch |
| Contact Operation | 1 step |
| Certifications | UL Listed CSA |
| Cable Entry | 0.75 inch NPT conduit entrance |
| Contact Arrangement | SPDT |
| Enclosure Rating | NEMA 2/4/13 |
| Voltage Rating | 600 V AC/DC |
| Protection | Oversized pedal shield Safety door Side shield |
| Operator Action | Spring return |
| Rated Breaking Capacity | 15 A 120 V AC inductive control circuit UL 508 10 A 240 V AC inductive control circuit UL 508 6 A 480 V AC inductive control circuit UL 508 5 A 600 V AC inductive control circuit UL 508 15 A 120 V AC resistive control circuit UL 508 0.5 A 125 V DC resistive control circuit UL 508 |
| Height | 6.3 in (159 mm) |
| Width | 6.4 in (163 mm) |
| Depth | 8.5 in (217 mm) |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CS121441 |
| Discount Schedule | OCS1 |
| GTIN | 785901652410 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|-------------------------------------|-----------------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.50 in (16.510 cm) |
| Package 1 Width | 6.80 in (17.272 cm) |
| Package 1 Length | 11.30 in (28.702 cm) |
| Package 1 Weight | 11.451 lb(US) (5.194 kg) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 36 |
| Package 2 Height | 40.00 in (101.600 cm) |
| Package 2 Width | 40.00 in (101.600 cm) |
| Package 2 Length | 48.00 in (121.920 cm) |
| Package 2 Weight | 415.999 lb(US) (188.694 kg) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

| | |
|--|-----------|
| Carbon footprint (kg CO ₂ eq, Total Life cycle) | 38 |
|--|-----------|

| | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
|--------------------------|---|

Use Better

Materials and Substances

| | |
|--|------------|
| Packaging made with recycled cardboard | Yes |
|--|------------|

| | |
|--------------------------------------|------------|
| Packaging without single use plastic | Yes |
|--------------------------------------|------------|

| | |
|-------------------|---|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
|-------------------|---|

| | |
|------------------|-----------------------------------|
| REACH Regulation | REACH Declaration |
|------------------|-----------------------------------|

| | |
|-----------------------|--|
| China RoHS Regulation | China RoHS declaration |
|-----------------------|--|

California proposition 65

WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture

Circularity Profile

No need of specific recycling operations

Take-back

No

Image of product / Alternate images

Alternative







