

# Product datasheet

Specifications



## Remote indication auxiliary, Acti9, iACTs, 1 NO + 1 NC

A9C15914

### Main

range of product	ICT
Range	Acti9
Device short name	iACTs
product or component type	Remote indication auxiliary
Signal contacts composition	1 NO + 1 NC

### Complementary

Signalling circuit voltage	24 V AC/DC: 10 mA 230 V AC: 50/60 Hz 5 A 230 V AC: 50/60 Hz 2 A 130 V DC: 1 A
[Uc] control circuit voltage	24...240 V AC 50/60 Hz 24...130 V DC
Range compatibility	Acti 9 Acti9 iCT
[Ui] rated insulation voltage	440 V
[Uimp] rated impulse withstand voltage	4 kV
mounting mode	Fixed, on the right of CT
mounting support	35 mm symmetrical DIN rail
9 mm pitches	1
Height	81 mm
Width	9 mm
Depth	68 mm
colour	White
Auxiliary connection terminal	Tunnel type terminals2 cable(s) flexible 2.5 mm <sup>2</sup> Tunnel type terminals2 cable(s) rigid 1.5 mm <sup>2</sup> Tunnel type terminals1 cable(s) rigid 1.5...2.5 mm <sup>2</sup> Tunnel type terminals1 cable(s) flexible 1.5...2.5 mm <sup>2</sup>
Wire stripping length	9 mm
Tightening torque	0.8 N.m
Product compatibility	ICT
Market segment	Small commercial Residential
compatibility code	iACTs

### Environment

<b>Standards</b>	EN 60947-5
<b>IP degree of protection</b>	IP20
<b>Tropicalisation</b>	2
<b>Relative humidity</b>	95 % at 55 °C
<b>Ambient air temperature for operation</b>	-5...50 °C
<b>Ambient air temperature for storage</b>	-40...70 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	2.2 cm
<b>Package 1 Width</b>	7.5 cm
<b>Package 1 Length</b>	8.5 cm
<b>Package 1 Weight</b>	43.0 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	8.1 cm
<b>Package 2 Width</b>	9.3 cm
<b>Package 2 Length</b>	22.8 cm
<b>Package 2 Weight</b>	490.0 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	120
<b>Package 3 Height</b>	30.0 cm
<b>Package 3 Width</b>	30.0 cm
<b>Package 3 Length</b>	40.0 cm
<b>Package 3 Weight</b>	6.36 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability


**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[How we assess product sustainability >](#)

## Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Scip Number** 429095ee-388a-4184-bea4-16f87e374975