Product data sheet
Characteristics

MG2C9
Powerpact 4 - panelboard - 250A - 9 ways - 3P - Style C

Main

Range of product	Powerpact 4
Range	PowerPact
Product or component-type	Panelboard
Product name	PowerPact 4
Device application	Distribution
Colour	Cream RAL 9001
Provided equipment	End cover Removable bottom gland plate

Complementary

[In] rated current	250 A
Number of ways	27 1P 9 3P
[Ue] rated operational voltage	415 V 50 Hz AC
Breaking capacity	36 kA AC 1 s
Enclosure material	Steel epoxy-polyester powder
Thickness	1.2 mm cover 1.6 mm enclosure
Cable entry	Bottom main
Device mounting	Wall mounted
Height	889 mm
Width	850 mm
Depth	260 mm
Horizontal fixing centres	670 mm
Vertical fixing centres	751 mm

Environment

IP degree of protection	IP3x
Standards	BS EN 60439-1

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0850 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months

Product Life Status : Commercialised

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.