



Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 x lamp 1 x fixing elements
Power factor	0.9

Complementary

Outlet standard	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	230 V AC - 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-in switch
Luminous flux	640 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m not supplied Cable quick connector 1 m not supplied
Mounting support	DIN rail Metal parts Bracket
Fixing mode	Clip-in Screws Magnetic fixing
Range compatibility	Spacial Thalassa
Material	PC (UL94 V-0)
Length	372 mm
Height	63 mm
Width	40 mm
Colour	Black RAL 9005

Environment

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class II
Electromagnetic compatibility	EMC immunity conforming to EN 55015
Standards	EN 55015 UL 94 UL 508 A IEC 60598 UL 1598 UL 8750
Ambient air temperature for operation	-16...65 °C
Ambient air temperature for storage	-10...60 °C

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold