

Product datasheet

Specifications



PP-B 16A 1P 35kA EverLink -TM

PP41P016

EAN Code: 5018934026619

Main

Range of product	PowerPacT 4
Product or component type	Circuit breaker
Device application	Distribution
Poles description	1P
[In] rated current	15 A at 40 °C
[Ue] rated operational voltage	230 V AC 50/60 Hz
[Icu] rated ultimate short-circuit breaking capacity	35 kA Icu at 230 V AC 50/60 Hz
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle

Complementary

Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	15 A at 40 °C
Earth-leakage protection	Without

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	15.500 cm
Package 1 Length	21.500 cm
Package 1 Weight	538.000 g

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

Use Again

Repack and remanufacture

Take-back	No
-----------	----