

Product datasheet

Specifications



Molded case circuit breaker (MCCB), Powerpact 4, thermal magnetic, single pole, 30A, 35kA, with Everlink connections

PP41P030

EAN Code: 5018934026640

Main

Range of product	PowerPacT 4
Product or component type	Circuit breaker
Device application	Distribution
poles description	1P
[In] rated current	30 A at 40 °C
[Ue] rated operational voltage	230 V AC 50/60 Hz
[Icu] rated ultimate short-circuit breaking capacity	35 kA Icu at 230 V AC 50/60 Hz
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle

Complementary

Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	30 A at 40 °C
Earth-leakage protection	Without

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	15.500 cm
Package 1 Length	22.000 cm
Package 1 Weight	538.000 g

Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications