

Product datasheet

Specifications



Switch disconnecter, PowerPacT 4, top entry, 3 poles, 400A

PP44003NATX

EAN Code: 5018934030449

Main

Range	PowerPact
Product or component type	Switch disconnecter
Device application	Isolation
poles description	3P
[In] rated current	400 A
[Ue] rated operational voltage	415 V AC 50/60 Hz
Suitability for isolation	Yes conforming to BS EN 60947-3
Utilisation category	AC-22A AC-23A
Contact position indicator	Yes
[Icw] rated short-time withstand current	5000 A during 1 s 5000 A during 3 s 1930 A during 20 s
[Icm] rated short-circuit making capacity	7.1 kA peak
Control type	Toggle
[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV

Complementary

product destination	400/630 A panelboard
Breaking capacity code	NA
Earth-leakage protection	Without
Mounting support	Backplate
Location of connection	Top entry
Mechanical durability	15000 cycles
Electrical durability	10000 cycles 440 V In/2 5000 cycles 440 V In
Width (W)	140 mm
Height (H)	255 mm
Depth (D)	110 mm
Net weight	5.2 kg

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	BS EN 60947-3
IP degree of protection	IP40 conforming to EN/IEC 60529
IK degree of protection	IK07 conforming to EN/IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to EN/IEC 60664-1
Ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	26 cm
Package 1 Length	39.5 cm
Package 1 Weight	7.474 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	72
Package 2 Height	112 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	576.64 kg

Contractual warranty

Warranty	18 months
----------	-----------