



SPECIFICATION SHEET

Product Code CMA017 Description 20A Flex Outlet Plate





DC E722

General Information	
Dimensions	86mm x 86mm x 9.5mm
Material composition	Front Plate: Urea
	Terminals: Brass
	Earth Strap: Mild Steel
	Terminal Screws: Steel and Yellow Passivated
	Silver "on-lay" copper/brass contacts.
Back Box Depth	16mm – 47mm
Cable Size	4 x 2.5mm ² or 1 x 6mm ²
Terminal Size	Live: 5mm
	Neutral: 5mm
	Earth: 5mm
Twin Earth	Yes
Flex Outlet	Yes (Centre of Plate or Through The Bottom)
Neon	No
Warranty	20 Years Domestic

Standards	BS 5/33
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella
	Pneumoniae
	Flex Outlet Diameter: 10mm

Staffordshire, B79 7XB.