

**SPECIFICATION SHEET**

Product Code

VP\*051#

Description

13A Fused Connection Unit Switched With Flex Outlet



General Information	
Dimensions	88mm x 88mm x 8mm (Excluding Gasket)
Finishes Available	Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass), CH (Polished Chrome), PN (Pearl Nickel), SB (Satin Brass), SC (Satin Chrome), and SS (Stainless Steel).
Inserts Available	Replace # with: WH (White) and BK (Black). Black or White gasket supplied to match appropriate inserts. (Antique Brass and Black Nickel are only available with back inserts).
Material Composition	Rear Housing: Nylon Front Plate: Stainless Steel Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Back Box Depth	35mm – 47mm
Cable Size	4 x 2.5mm <sup>2</sup>
Terminal Size	Live: 5mm Neutral: 5mm Earth: 5mm
Switched	Yes
Double Pole	Yes
Twin Earth	Yes
Flex Outlet	Yes
Neon	No
Warranty	10 Years Domestic
Standards	
	BS 1363 BS 1362 (Fuse)
Additional Information	
	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Flex Outlet Diameter: 10mm