

Technical Data Sheet

FrogTape® for Gloss & Satin Paints Masking Tape

A medium tack masking tape for use when painting skirting boards, architraves, frames & doors



Properties

- Should only be applied to cured surfaces
- Can be applied for up to 21 days before you paint
- UV resistant and can be applied for up to 7 days if in direct sunlight
- With PaintBlock® Technology - Reduces paint bleed
- Remove immediately after painting

Area of Use

- Use to protect surfaces when using Gloss or Satin paint
- Available in 24mm and 36mm widths
- Available in 41.1m length

Technical Data

Thickness mm	: 0,15
Adhesive	: Acrylic
Adhesion to Stainless Steel N/10mm	: 3,61
Tensile Strength N/10mm	: 38,5
Elongation	: 8%
Service Temperature Min	: 10°C
Service Temperature Max	: 66°C

Application Overview

Application	Suitability
Inside	<input type="checkbox"/>
Outside	<input type="checkbox"/>
Cured Paint (dried 3 days min.)	<input type="checkbox"/>
Gloss & Satin Paints	<input type="checkbox"/>
Windows, Glass	<input type="checkbox"/>
Carpet, Stone	<input type="checkbox"/>

suitable

Storage and Usage Conditions

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Physical and performance characteristics shown above are obtained by tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Services Department and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages.

The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.