

Technical Data Sheet

Duck® Tape Original

The original Duck® Tape – A general purpose Cloth Duct Tape



Properties

- Waterproof backing
- Good adhesion
- Excellent conformability
- Good handling characteristics – does not twist or curl during application
- Available in a variety of widths and lengths

Area of Use

- Repairs, seals, reinforces, protects, binds holds and identifies

Colours



Silver



Black



White



Green

Technical Data

Thickness mm	: 0,20
Backing	: Waterproof polyethylene film with a cloth carrier
Adhesive	: Natural Rubber
Adhesion to Stainless Steel N/10mm	: 6,02
Tensile Strength N/10mm	: 35,0
Elongation:	: 20%
Service Temperature Range	: 10°C to 93°C

Storage and Usage Conditions

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

Physical and performance characteristics shown above are obtained by tests recommended by PTSC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Services Department and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages.

The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.