

RCBO, 10 kA, 1P+N, Type A, 30 mA, B char., In: 32 A, Un AC: 230 V, pigtail 600 mm, solid N

Model	
product brand name	SENTRON
product designation	RCD-operated circuit breaker
design of the product	Instantaneous
General technical data	
number of poles	2
number of poles / with protection	1
design of pole	1P+N
tripping characteristic class	B
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage / of the operating voltage	AC
insulation voltage (Ui) / rated value	264 V
surge voltage resistance / rated value	4 000 V
surge current resistance / at (8/20) μs	1 kA
Supply voltage	
supply voltage	
• at AC / rated value	230/240 V
• for testing equipment / minimum	115 V
operating frequency	50/60 Hz
supply voltage frequency / rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Switching capacity	
breaking capacity short-circuit current (Icn) / according to EN 61009-1 / rated value	10 kA
switching capacity current	
• according to EN 60898 / rated value	10 kA
• according to IEC 60947-2 / rated value	10 kA
rated residual switching capacity (IΔm) / according to IEC 61009-1	10 kA
energy limitation class	3
Current	
tripping fault current / rated value	30 mA
operational current	
• at 30 °C / rated value	20 A
• at AC / rated value	20 A
residual current type	A
Connections	
connectable conductor cross-section / using the upper clamping point / without core end processing	
• minimum	0.75 mm ²
• maximum	16 mm ²
connectable conductor cross-section / solid	
• minimum	0.75 mm ²
• maximum	35 mm ²
connectable conductor cross-section / stranded	
• minimum	0.75 mm ²

<ul style="list-style-type: none"> • maximum 	35 mm ²
connectable conductor cross-section / finely stranded / with core end processing	
<ul style="list-style-type: none"> • minimum • maximum 	0.75 mm ² 25 mm ²
tightening torque / with screw-type terminals	
<ul style="list-style-type: none"> • minimum • maximum 	1.2 N·m 2 N·m
position / of power supply cord	Either top or bottom
Mechanical Design	
height	125 mm
width	18 mm
depth	77 mm
installation depth	70 mm
number of modular width units	1
mounting position	any
Environmental conditions	
influence of the surrounding temperature	Max. 95% humidity
ambient temperature / during operation	
<ul style="list-style-type: none"> • minimum • maximum 	-25 °C 55 °C
ambient temperature / during storage	
<ul style="list-style-type: none"> • minimum • maximum 	-40 °C 75 °C
number of test cycles / for environmental testing / according to IEC 60068-2-30	28
Certificates	
reference code	
<ul style="list-style-type: none"> • according to EN 61346-2 • according to IEC 81346-2 	F F
General Product Approval	

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU9304-6KK32>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU9304-6KK32>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU9304-6KK32

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



