

SLA3400

FA/LA MOLDED CASE CIRCUIT BREAKER, 415/240V, 400A, 3P



Main

Product or component-type	Circuit breaker
Range of product	Square D
Trip unit technology	Thermal-magnetic
Breaking capacity code	A

Complementary

[In] rated current	400 A
Poles description	3P
Breaking capacity	65 kA at 240 V AC 10 kA at 250 V DC 36 kA at 415 V AC
[Ue] rated operational voltage	750 V AC 250 V DC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 1...600 kcmil (aluminium/copper) 1 cable(s) AWG 1...250 kcmil (aluminium/copper) 2 cable(s)
Terminal identifier	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Height	12.6 in
Width	12.5 in
Depth	19.9 in

Environment

Product certifications	CE IEC
Ambient air temperature for operation	40 °C

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold

Product Life Status : **Commercialised**

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.